



# LamaPLC: SC16IS750 / SC16IS752: One or two serial (UART) ports from microcontroller via I<sup>2</sup>C or SPI communication

The **CJMCU-750** is a breakout board that houses the **NXP SC16IS750** chip, a high-performance **UART** (*Universal Asynchronous Receiver/Transmitter*) with a single channel and support for either **I<sup>2</sup>C** or **SPI** interfaces. It is often used to add a serial port to microcontrollers. The **CJMCU-752** also includes the **NXP SC16IS752** IC.

The primary difference between the **SC16IS750** and **SC16IS752** is the number of UART channels: the SC16IS750 is a single-channel UART, while the SC16IS752 is a dual-channel UART. Both chips convert I<sup>2</sup>C or SPI bus signals to serial ports and share many other features.

## Comparison of SC16IS750 and SC16IS752

		
<b>Feature</b>	NXP SC16IS750 <b>CJMCU-750</b>	NXP SC16IS752 <b>CJMCU-752</b>
<b>UART Channels</b>	Single full-duplex UART	Dual full-duplex UART
<b>Host Interface</b>	Selectable I <sup>2</sup> C or SPI	Selectable I <sup>2</sup> C or SPI
<b>FIFOs</b>	64-byte transmit/receive	64-byte transmit/receive per channel
<b>Baud Rate</b>	Up to 5 Mbit/s	Up to 5 Mbit/s
<b>SPI Clock Speed</b>	Up to 4 Mbit/s	Up to 4 Mbit/s
<b>Programmable I/O</b>	8 GPIO pins	8 GPIO pins
<b>Compatibility</b>	16C450 industrial standard	16C450 industrial standard
<b>Operating Voltage</b>	2.5 V or 3.3 V (5 V tolerant inputs)	2.5 V or 3.3 V (5 V tolerant inputs)
<b>Packages</b>	HVQFN24, TSSOP24	HVQFN32, TSSOP28

## Key Features and Specifications

- **Function:** Converts I<sup>2</sup>C-bus or SPI signals to a single full-duplex UART (Universal Asynchronous Receiver/Transmitter) for protocol conversion.
- **Interfaces:** Features selectable I<sup>2</sup>C (up to 400 kHz) or SPI (up to 4 Mbit/s) interfaces.
- **UART Data Rates:** Supports baud rates up to 5 Mbit/s in 16x clock mode.
- **FIFO:** Includes 64 bytes of transmit and receive FIFOs.
- **Programmable I/O:** Provides 8 additional programmable I/O pins, which can be accessed via the I<sup>2</sup>C or SPI interface.
- **Compatibility:** Fully compatible with the industrial standard 16C450 and equivalent devices.
- **Operating Voltage:** Operates on a 3.3 V or 2.5 V supply and logic levels.
- **Flow Control:** Supports auto hardware flow control (RTS/CTS) and auto software flow control (programmable Xon/Xoff characters).

- **Applications:** Ideal for industrial control, portable devices, and battery-operated applications due to its low power consumption and compact design.




If you'd like to support the development of the site with the price of a coffee — or a few — [please do so here](#).

Here's a handy tip: you can quickly save this page as a PDF by clicking "export to PDF" in the menu on the right side of the screen.

2026/02/14 23:38

## CJMCU-752 Pinout



Pin Number	Pin Name	Description
1	A0	I <sup>2</sup> C address selection or SPI chip select
2	A1	I <sup>2</sup> C address selection or SPI chip select
3	RESET	Active-low reset input
4	XTAL1	Crystal oscillator input or external clock input
5	XTAL2	Crystal oscillator output
6	VSS	Ground
7	TXB	UART channel B transmit output
8	RXB	UART channel B receive input
9	RTSB	UART channel B request-to-send output
10	CTSB	UART channel B clear-to-send input
11	GPIO0	General-purpose I/O pin
12	GPIO1	General-purpose I/O pin
13	GPIO2	General-purpose I/O pin
14	GPIO3	General-purpose I/O pin
15	GPIO4	General-purpose I/O pin
16	GPIO5	General-purpose I/O pin
17	GPIO6	General-purpose I/O pin
18	GPIO7	General-purpose I/O pin
19	CTSA	UART channel A clear-to-send input
20	RTSA	UART channel A request-to-send output
21	RXA	UART channel A receive input
22	TXA	UART channel A transmit output
23	VSS	Ground

Pin Number	Pin Name	Description
24	VCC	Power supply input
25	SCL/SCLK	I <sup>2</sup> C clock input or SPI clock input
26	SDA/MOSI	I <sup>2</sup> C data input/output or SPI master-out/slave-in
27	A2/MISO	I <sup>2</sup> C address selection or SPI master-in/slave-out
28	CS	SPI chip select (active low)

### How to Use the SC16IS752 in a Circuit

- **Power Supply:** Connect the VCC pin to a 3.3V power source and the VSS pins to ground.
- **Clock Source:** Use an external crystal oscillator (e.g., 14.7456 MHz) connected to XTAL1 and XTAL2, or provide an external clock signal to XTAL1.
- **Communication Protocol Selection:**
  - **For I<sup>2</sup>C:** Connect SCL and SDA to the microcontroller's I<sup>2</sup>C pins. Use A0, A1, and A2 to set the I<sup>2</sup>C address.
  - **For SPI:** Connect SCLK, MOSI, MISO, and CS to the microcontroller's SPI pins.
- **UART Connections:** Connect TXA/RXA and TXB/RXB to the respective UART devices. Use RTS and CTS for hardware flow control if needed.
- **GPIO Configuration:** Configure GPIO pins as inputs or outputs as required by your application.

### Important Considerations and Best Practices

- Add pull-up resistors (usually 4.7kΩ) to the I<sup>2</sup>C lines (SCL and SDA).
- Place a 0.1 μF capacitor near the VCC pin to decouple the power supply.
- Properly terminate SPI lines to maintain signal integrity.
- Set the baud rate and UART parameters through the SC16IS752's internal registers.
- Use the RESET pin to initialize the device during power-up or fault recovery.

### CJMCU-752 Set I<sup>2</sup>C address

The I<sup>2</sup>C address of the CJMCU-752 (SC16IS752) is determined by the logic levels of the A0 and A1 pins. These pins can be tied to VDD (VCC), VSS (GND), SCL, or SDA, allowing for up to 16 unique addresses on a single bus.

For most Arduino and Raspberry Pi libraries, you must use the 7-bit address. The default configuration (both pins pulled High) is typically **0x48**.

A1 Pin	A0 Pin	7-bit Address	8-bit Write Address
VDD	VDD	<b>0x48</b>	0x90
VDD	VSS(GND)	0x49	0x92
VSS(GND)	VDD	0x4C	0x98
VSS(GND)	VSS(GND)	0x4D	0x9A

### Important Implementation Notes

- **Address Shifting:** Hardware documentation often lists addresses in 8-bit format (e.g., 0x90). To get the 7-bit address used in `Wire.begin()`, shift the value one bit to the right ( $0x90 \gg 1 = 0x48$ ).
- **Interface Selection:** Ensure the I<sup>2</sup>C/SPI pin is tied High to enable I<sup>2</sup>C mode; otherwise, these pins may function differently for SPI communication.

- **A0 Sharing:** In SPI mode, the A0 pin functions as the Chip Select (CS) line.

## Arduino

### Wiring

Ensure the I2C/SPI pin on the module is tied to High (3.3V) to enable I<sup>2</sup>C mode.

- **VCC:** 5V (Board has an on-board 3.3V regulator)
- **GND:** GND
- **SDA:** Arduino A4 (Uno) or SDA pin
- **SCL:** Arduino A5 (Uno) or SCL pin
- **A0/A1:** Tie to VCC for default address **0x90** (check your specific module's documentation, as some use **0x48**).

To use the CJMCU-752 with an Arduino, the most reliable approach is to use the **Appnestic SC16IS7XX** Library, which supports both the single-channel '**750**' and dual-channel '**752**' variants over I<sup>2</sup>C and SPI.

### Arduino 1st code: Check channels

```
#include <Wire.h>
#include <SC16IS7xx.h>

// Initialize for I2C with address 0x90 (adjust if your module uses 0x48)
SC16IS7xx dualUart = SC16IS7xx(SC16IS7xx_PROTOCOL_I2C, 0x90);

void setup() {
  Serial.begin(115200);

  // Initialize both UART channels (A and B) at 9600 baud
  dualUart.a().begin(9600);
  dualUart.b().begin(9600);

  Serial.println("SC16IS752 Dual UART Initialized");
}

void loop() {
  // Example: Bridge Channel A data to Channel B
  if (dualUart.a().available()) {
    char c = dualUart.a().read();
    dualUart.b().write(c); // Echo to the other channel
    Serial.print("Channel A received: ");
    Serial.println(c);
  }

  // Example: Bridge Channel B data back to A
  if (dualUart.b().available()) {
```

```

char c = dualUart.b().read();
dualUart.a().write(c);
Serial.print("Channel B received: ");
Serial.println(c);
}
}

```

## Key Implementation Details

- **Dual Channels:** Use `.a()` and `.b()` methods to target specific serial ports on the SC16IS752.
- **Crystal Frequency:** Most CJMCU boards use a 14.7456 MHz crystal. If your baud rates seem incorrect, verify your crystal and use `dualUart.setCrystalFrequency(14745600);` before `begin()`.
- **5V Tolerance:** The chip operates at 3.3V, but the input pins are 5V tolerant, making it safe for direct connection to an Arduino Uno.

## Arduino 2nd code: Use GPIO

To use GPIO0 on the CJMCU-752 (SC16IS752) with an Arduino, you treat the chip as an I/O expander via the same I<sup>2</sup>C or SPI interface used for the UART channels.

On the CJMCU-752 board, look for the pin labeled GP0 or GPIO0.

- **Role:** This is one of 8 programmable I/O pins (GPIO0–GPIO7).
- **Voltage:** While the board is 5V tolerant, these pins typically operate at 3.3V logic levels.

The **Appnestic SC16IS7XX** library provides direct methods to control these pins without needing manual register writes.

```

#include <Wire.h>
#include <SC16IS7xx.h>

// Use address 0x90 (7-bit 0x48) for I2C
SC16IS7xx dualUart = SC16IS7xx(SC16IS7xx_PROTOCOL_I2C, 0x90);

void setup() {
  Serial.begin(115200);

  // Set GPIO0 as an OUTPUT
  // The second argument is the pin number (0-7)
  dualUart.pinMode(0, OUTPUT);
}

void loop() {
  // Turn GPIO0 High
  dualUart.digitalWrite(0, HIGH);
  Serial.println("GPIO0 HIGH");
  delay(1000);

  // Turn GPIO0 Low

```

```

dualUart.digitalWrite(0, LOW);
Serial.println("GPIO0 LOW");
delay(1000);
}

```

If you are writing your own driver, GPIO0 is controlled via the IOControl, IODir, and IOState registers:

- **Direction:** Set bit 0 of the IODir register (0 = Input, 1 = Output).
- **State:** Read or write bit 0 of the IOState register to interact with the physical pin.
- **Latching:** Ensure the IOControl register is configured to enable GPIO functions rather than special UART functions (like modem signals).

**Note on SC16IS752 vs 750:** In the dual-channel SC16IS752, the GPIO pins are shared and managed at the device level, not per-channel.

## I<sup>2</sup>C topics on lamaPLC

Page	Date	Tags
• <a href="#">lamaPLC Communication: 1-Wire</a>	2026/04/23 21:51	<a href="#">1-wire</a> , <a href="#">communication</a> , <a href="#">bus</a> , <a href="#">microlan</a> , <a href="#">i2c</a> , <a href="#">uart</a> , <a href="#">usart</a> , <a href="#">ds18b20</a>
• <a href="#">lamaPLC Communication: I<sup>2</sup>C</a>	2025/09/23 21:25	<a href="#">i2c</a> , <a href="#">i c</a> , <a href="#">smbus</a> , <a href="#">philips</a> , <a href="#">bus</a> , <a href="#">communication</a> , <a href="#">arduino</a>
• <a href="#">lamaPLC project: Sension SCD CO<sup>2</sup> measurement module</a>	2026/04/15 19:34	<a href="#">scd30</a> , <a href="#">scd40</a> , <a href="#">scd41</a> , <a href="#">iaq</a> , <a href="#">ndir</a> , <a href="#">sensor</a> , <a href="#">i2c</a> , <a href="#">arduino code</a>
• <a href="#">LamaPLC: AHT10 Modul</a>	2026/03/22 03:14	<a href="#">communication</a> , <a href="#">i2c</a> , <a href="#">temperature</a> , <a href="#">humidity</a> , <a href="#">sensor</a> , <a href="#">aht</a> , <a href="#">aht 10</a> , <a href="#">modul</a>
• <a href="#">LamaPLC: AHT20 / BMP280 Modul</a>	2026/04/23 21:52	<a href="#">bmp280</a> , <a href="#">aht20</a> , <a href="#">adafruit</a> , <a href="#">temperature</a> , <a href="#">humidity</a> , <a href="#">pressure</a> , <a href="#">sensor</a> , <a href="#">arduino</a> , <a href="#">code</a> , <a href="#">i2c</a>
• <a href="#">LamaPLC: APDS - Avago ALS and proximity detection sensors with I<sup>2</sup>C communication</a>	2026/04/23 21:52	<a href="#">avago</a> , <a href="#">apds-9900</a> , <a href="#">apds-9930</a> , <a href="#">apds-9960</a> , <a href="#">als</a> , <a href="#">proximity</a> , <a href="#">detection</a> , <a href="#">gesture recognition</a> , <a href="#">gesture</a> , <a href="#">i2c</a> , <a href="#">communication</a> , <a href="#">sensor</a> , <a href="#">arduino</a> , <a href="#">code</a>
• <a href="#">lamaPLC: Arduino Modul: BME680</a>	2026/05/12 18:40	<a href="#">code</a> , <a href="#">c</a> , <a href="#">2026</a> , <a href="#">arduino</a> , <a href="#">bme680</a> , <a href="#">sensor</a> , <a href="#">i2c</a> , <a href="#">comunication</a>
• <a href="#">lamaPLC: AS5600 Magnetic Induction Angle Measurement Sensor Module</a>	2026/05/13 00:06	<a href="#">communication</a> , <a href="#">i2c</a> , <a href="#">as5600</a> , <a href="#">as-5600</a> , <a href="#">magnetic</a> , <a href="#">induction</a> , <a href="#">angle</a> , <a href="#">sensor</a>
• <a href="#">lamaPLC: Bi-Directional Logic Level Converter 3.3V ↔ 5V</a>	2026/04/12 00:34	<a href="#">bi-directional</a> , <a href="#">logic level converter</a> , <a href="#">i2c</a> , <a href="#">uart</a> , <a href="#">spi</a>
• <a href="#">LamaPLC: BMP/BME Bosch Temperature/Humidity/Pressure sensors with I<sup>2</sup>C communication</a>	2026/04/23 21:52	<a href="#">bme280</a> , <a href="#">bme680</a> , <a href="#">bme688</a> , <a href="#">bmp180</a> , <a href="#">bmp280</a> , <a href="#">hw-611</a> , <a href="#">hw611</a> , <a href="#">bosch</a> , <a href="#">temperature</a> , <a href="#">humidity</a> , <a href="#">pressure</a> , <a href="#">sensor</a> , <a href="#">arduino</a> , <a href="#">i2c</a> , <a href="#">communication</a> , <a href="#">ai</a> , <a href="#">cjmcu</a> , <a href="#">volatile organic compounds</a> , <a href="#">vocs</a> , <a href="#">volatile sulfur compounds</a> , <a href="#">vscs</a> , <a href="#">iaq</a>
• <a href="#">LamaPLC: CJMCU-219/INA-219 breakout board/IC with I<sup>2</sup>C communication</a>	2026/04/23 21:52	<a href="#">cjmcu-219</a> , <a href="#">ina-219</a> , <a href="#">ina219</a> , <a href="#">breakout board</a> , <a href="#">i2c</a> , <a href="#">communication</a> , <a href="#">sensor</a> , <a href="#">voltage</a> , <a href="#">current</a> , <a href="#">arduino</a> , <a href="#">code</a> , <a href="#">cjmcu</a>

- [LamaPLC: CJMCU-3216 / AP-3216 integrated digital ambient light and proximity sensor module/IC with I<sup>2</sup>C communication](#) 2026/04/23 21:52 [cjmcu-3216, cjmcu, ap-3216, ap3216, ambient light, proximity, sensor, arduino, code, i2c, communication](#)
- [lamaPLC: CJMCU-811 CCS811 Gas Sensor \(VOCs TVOC CO2\)](#) 2026/04/23 21:52 [cjmcu-811, ccs811, gas, sensor, vocs, tvoc, eco2, co2, arduino, air quality metal oxide, mox, i2c, micropython, rp2040-eth](#)
- [LamaPLC: D6T Omron Non-Contact Thermal Sensors with I<sup>2</sup>C communication](#) 2026/04/23 21:52 [d6t, d6t-32l, d6t-44l, d6t-8l, d6t-1a, omron, non-contact, thermal, sensor, i2c, arduino, code](#)
- [LamaPLC: DPS Infineon Temperature/Pressure sensors with I2C communication](#) 2026/04/23 21:52 [dps310, infineon, temperature, pressure, sensor, arduino, i2c, communication, code](#)
- [lamaPLC: Energy, power, current, and voltage](#) 2025/05/31 23:32 [i2c, i c, communication, arduino, energy, power, current, sensor, ina226](#)
- [LamaPLC: ENS ScioSense Multi-gas sensors with I<sup>2</sup>C communication](#) 2026/04/23 21:52 [ens160, sciosense, gas-quality, i2c, communication, sensor, arduino, code, eco2, tvoc, aqi, indoor air quality, iaq, co2, voc](#)
- [lamaPLC: ESP32 / ESP8266](#) 2025/11/22 00:07 [esp8266, esp32, esp32-c2, esp32-c3, esp32-c5, esp32-c6, esp32-c61, esp32-h2, esp32-s2, esp32-s3, esp32-p4, espressif systems, communication, ethernet, ip, wi-fi, thread, zigbee, matter, homekit, bluetooth, mqtt, adc, spi, uart, i2c, i2s, rmt, pwm, usb, usb otg, twai](#)
- [LamaPLC: Gas sensors](#) 2023/07/01 17:29 [gas, sensor, i2c, onewire, communication, mq-3, mq-4, mq-5, mq-6, mq-7, mq-8, mq-9, mq-135, gm-102b, gm-302b, gm-502b, gm-702b, alcohol, ch4, natural gas, smoke, lng, co, co2, lpg, h2, iso-butane, nox, nh3, benzene, town gas, formaldehyde, propane, humidity, temperature, voc, grv gas sens v2](#)
- [lamaPLC: GY-511 6DOF sensor module](#) 2026/04/23 21:52 [stmicroelectronics, lsm303dlhc, i2c, lsm303, sensor, gy-511, 6dof, pololu, module, arduino](#)
- [LamaPLC: GY-9250 MPU-9250/6500 9-axis Attitude Sensor Board](#) 2026/04/23 21:52 [ak8963, gy-9250, mpu-9250, 9-axis, motion detection, magnetometer, communication, i c, i2c, spi](#)
- [LamaPLC: HDC Texas Instruments Temperature/humidity sensors with I<sup>2</sup>C communication](#) 2026/04/23 21:52 [sht21, htu21, si7021, gy-21, gy-213v, hdc1080, gy-213v-hdc1080, cjmcu, cjmcu-1080, texas instruments, temperature, humidity, sensor, i2c, communication, arduino, code](#)
- [lamaPLC: HT16K33 display controller](#) 2026/04/23 21:51 [i2c, 7-segment display, display, ht16k33, arduino](#)

<ul style="list-style-type: none"> <li>• <a href="#">LamaPLC: HTU TE Connectivity temperature/humidity sensors with I<sup>2</sup>C communication</a></li> </ul>	2026/04/23 21:52	htu, htu31d, htu21d, htu20d, sht20, htu20, sht21, htu21, si7021, gy-21, gy-213v, hdc1080, si702, gy-20, sht31, htu31, si7031, gy-31, te connectivity, temperature, humidity, i2c, communication, sensor, arduino, code
<ul style="list-style-type: none"> <li>• <a href="#">lamaPLC: INA modules with Arduino libraries</a></li> </ul>	2026/04/23 21:52	energy, power, current, monitor, sensor, ina219, gy-219, ina226, gy-216, ina228, gy-228, ina237, ina238, ina260, ina3221, ina
<ul style="list-style-type: none"> <li>• <a href="#">lamaPLC: INA226 - current/voltage/power monitor with I<sup>2</sup>C communication</a></li> </ul>	2026/04/23 21:52	i2c, i c, communication, arduino, energy, power, current, monitor, sensor, ina226, ina219, ina
<ul style="list-style-type: none"> <li>• <a href="#">lamaPLC: LCD 1602/2004 with I<sup>2</sup>C communication</a></li> </ul>	2026/02/14 18:27	communication, i2c, display, lcd, 1602, 2004, hd44780, pcf8574, pcf8574t, pcf8574at, arduino
<ul style="list-style-type: none"> <li>• <a href="#">LamaPLC: MAX30100/MAX30102 Heart Rate Click Sensor Module</a></li> </ul>	2026/04/23 21:52	max30102, max30100, heart rate click, sensor, communication, i2c, arduino, code
<ul style="list-style-type: none"> <li>• <a href="#">lamaPLC: MCP23017 / MCP23S17 16-Bit I/O Expander with Serial Interface I<sup>2</sup>C / SPI</a></li> </ul>	2026/04/23 21:52	communication, i2c, mcp23017, mcp23s17, spi, i o expander, serial, cjmcu-2317, cjmcu
<ul style="list-style-type: none"> <li>• <a href="#">lamaPLC: MLX90614 (GY-906) infrared non-contact thermometer</a></li> </ul>	2026/05/08 00:03	communication, i2c, temperature, mlx90614, gy-906, modul, infrared, non-contact thermometer, dsp, pwm, smbus, hailege
<ul style="list-style-type: none"> <li>• <a href="#">lamaPLC: PCF857x I/O Expander chip/modul with I<sup>2</sup>C communication</a></li> </ul>	2026/05/15 01:03	communication, i2c, pcf857x, pcf8574, pcf8574a, pcf8575, i o expander, i o extension, nxp, texas instruments
<ul style="list-style-type: none"> <li>• <a href="#">LamaPLC: Pixart PAJ7620U2 Gesture recognition sensors/module with I<sup>2</sup>C communication</a></li> </ul>	2026/04/23 21:52	paj7620u2, gy-paj7620, pixart, gesture recognition, i2c, communication, sensor, arduino, code
<ul style="list-style-type: none"> <li>• <a href="#">lamaPLC: RP2040_ETH_Modul: I<sup>2</sup>C scanner</a></li> </ul>	2026/05/12 16:20	code, micropython, 2026, rp2040 eth, i2c, comunication
<ul style="list-style-type: none"> <li>• <a href="#">lamaPLC: RP2040_ETH_Modul: MLX90614 simple</a></li> </ul>	2026/05/12 17:06	code, micropython, 2026, rp2040 eth, i2c, communication, mlx90614
<ul style="list-style-type: none"> <li>• <a href="#">lamaPLC: RP2040_ETH_Modul: Read BME 680/688 sensor data</a></li> </ul>	2026/05/12 21:06	code, micropython, 2026, rp2040 eth, bme680, i2c, sensor, communication
<ul style="list-style-type: none"> <li>• <a href="#">lamaPLC: RP2040_ETH_Modul: Read BME 680/688 sensor data and store in Modbus input registers</a></li> </ul>	2026/05/12 18:58	code, micropython, 2026, rp2040 eth, bme680, i2c, sensor, communication
<ul style="list-style-type: none"> <li>• <a href="#">LamaPLC: SC16IS750 / SC16IS752: One or two serial (UART) ports from microcontroller via I<sup>2</sup>C or SPI communication</a></li> </ul>	2026/04/23 21:52	cjmcu-750, cjmcu-752, cjmcu, nxp, sc16is750, sc16is752, uart, serial, i2c, spi, modul, converter, arduino, code
<ul style="list-style-type: none"> <li>• <a href="#">LamaPLC: SGP Sensirion TVOC/VOC sensors with I<sup>2</sup>C communication</a></li> </ul>	2026/04/15 19:41	sgp30, sgp40, sgp41, sensirion, gas-sensor, i2c, communication, sensor, arduino, code, eco2, voc, tvoc, indoor air quality, iaq, nox, hydrogen

- LamaPLC: SHT Sensirion Temperature/humidity sensor with I<sup>2</sup>C communication

 2026/04/23  
21:52
 

 sht20, sht21, sht25, sht30, sht31, sht35, sht40, gy21, temperature, humidity, i2c, communication, sensor, arduino, code
  
- lamaPLC: Signal level converters

 2026/02/14  
23:47
 

 pca9306, i2c, voltage, level, converter
  
- lamaPLC: st756x display drivers

 2026/05/20  
16:17
 

 display, driver, i2c, spi, lcd, cog, oled, st7565, st7567, gm12864, gm12864-59n, gm12864-03a, gm12864-01a, gme12864-41
  
- lamaPLC: TCA9548A (HW617); Low-Voltage 8-Channel I<sup>2</sup>C Switch Module

 2026/02/14  
23:51
 

 tca9548a, hw617, i2c, switch, communication, expansion board, arduino
  
- lamaPLC: TM1637 7-segment display

 2026/02/14  
18:26
 

 i2c, 7-segment display, display, tm1637, arduino
  
- LamaPLC: TOFnnnC STMicroelectronics Time-of-Flight (ToF) sensors with I<sup>2</sup>C communication

 2026/04/23  
21:52
 

 tof050c, vl6180, tof200c, vl53l0x, tof400c, vl53l1x, stmicroelectronics, time-of-flight, tof, i2c, communication, sensor, arduino, code
  
- LamaPLC: VL53Lnn STMicroelectronics time-of-flight (ToF) laser-ranging sensors with I<sup>2</sup>C communication

 2026/04/23  
21:52
 

 vl53l0x, vl53l1x, vl53l0 1xv2, gy-530, time-of-flight, tof, laser-ranging, i2c, communication, sensor, arduino, code
  
- LamaPLC: VL6180X STMicroelectronics Time-of-Flight (ToF) sensor with I<sup>2</sup>C communication

 2026/04/23  
21:52
 

 vl6180x, stmicroelectronics, time-of-flight, tof, i2c, communication, sensor, arduino, code
  
- lamaPLC: XGZP68xx: Silicon Pressure Sensors/Module

 2026/05/15  
15:17
 

 communication, i2c, sensor, modul, pressure, cfsensor, xgzp68xx, xgzp6810d, xgzp6857d, xgzp6859d, xgzp6887d, xgzp6897d, xgzp6899a, piezoresistive, capacitive
  
- Magnetic angle sensors

 2026/04/23  
21:52
 

 magnetic angle sensor, magnetic flux, sensor, spi, i2c, pwm, communication, modul, as5047p, as5600, mt6701, mt6816, mt6835, tle5012b, amr, gmr, tmr, anisotropic magnetoresistive
  
- SSH1106/SSD1306 OLED Display with I<sup>2</sup>C communication

 2026/02/14  
18:27
 

 i2c, oled, display, ssd1306, sh1106, ssh1106, arduino, cmos

CJMCU-750, CJMCU-752, CJMCU, NXP, SC16IS750, SC16IS752, UART, serial, I2C, SPI, modul, converter, Arduino, code

This page has been accessed for: Today: 1, Until now: 302

From:  
<https://lamaplc.de/> - **lamaPLC**

Permanent link:  
[https://lamaplc.de/doku.php?id=sensor:sc16is750\\_752](https://lamaplc.de/doku.php?id=sensor:sc16is750_752)

Last update: **2026/04/21 20:47**



